

# ROOF MAGIC SPECIFICATION SHEET

## • Features

- For Concrete Tile, Clay Tile and Metal Roofs
- 100% Acrylic
- 7 Standard Colors
- Custom Colors Available
- One Primer/Sealer Coat
- Two Finish Coats
- 10 Yr. Limited Warranty

## • Coverage Rate Per Gallon

- Primer/Sealer Coat: 200 square feet
- Intermediate Coat: 300 square feet
- Finish Coat : 300 square feet

## • General Application Guidelines

- Pressure Wash
- Apply to clean, dry surface
- One Primer/Sealer Coat - *Drying Time: Overnight; Cure Time: 20 days*
- Two Finish Coats - *Drying Time: First coat 4 - 6 hours; Cure Time: 20 days*
- Application temperature range 45 - 90 degrees F.
- Clean-up with soap and water

### Primer:

Gloss:	Flat
Volume:	39.70%
Weight/gal:	12.09 lb.
Viscosity:	87-92 K.U.
Spread Rate:	200-sq. ft./gal.
Weight Solids:	58.40%
Light Reflection:	80%
Vehicle Type:	Acrylic Latex Resin

### Finish:

Gloss:	8-12 Sheen
Volume:	33.0%
Weight/gal:	11.65 lb.
Viscosity:	95-100 K.U.
Spread Rate:	300-sq. ft./gal.
Weight Solids:	52.50%
Light Reflection:	80% (white)
Vehicle Type:	Acrylic Resin